


1-Gang Boxes

Cast Aluminum FS Boxes
Non-Metallic FS Boxes


Cast Aluminum Weatherproof FS Boxes

FEATURES

- Electrostatically painted with a baked, weather-resistant powder finish for exceptional durability.
- Accept single gang weatherproof cover and standard FS covers.
- UL Listed for wet and damp locations with appropriate cover installed.
- Mounting lugs provide strength and durability on any mounting surface.
- Raised knockout studs on back of box provide alternative means for wall mounting. Strike desired studs with sharp hammer blow for clean mounting holes.
- Easy access ground screw hole located inside back wall of box.
- Threaded outlets for conduit and connectors.
- Two closure plugs and mounting lugs furnished.




1113




1117

1-Gang FS Boxes


Description	End Openings	Back Openings	Catalog No.	UL US
3 hole 0.50" (12.70mm) dia.	1-1	1	□ 1113	•
4 hole 0.50" (12.70mm) dia.	2-1	1	□ 1114	•
5 hole 0.50" (12.70mm) dia.	2-2	1	□ 1115	•
3 hole 0.75" (19.05mm) dia.	1-1	1	□ 1116	•
4 hole 0.75" (19.05mm) dia.	2-1	1	□ 1117	•
5 hole 0.75" (19.05mm) dia.	2-2	1	□ 1118	•




1113




1114




1115



1116



1117




1118

Non-Metallic Weatherproof FS Box

1-Gang FS Box

Product Description	Catalog No.	UL US
Black FS Box with (2) 0.75" (19.05mm) IPS molded-in knockouts	□ 6080	•



6080

Icon Key

NAFTA Compliant - see page O-30